



SITOP DC UPS MODULE 15A WITHOUT INTERF.
SITOP DC UPS MODULE 24 V/15 A UNINTERRUPTIBLE POWER
SUPPLY WITHOUT INTERFACE INPUT: 24 V DC/16 A OUTPUT:
24 V DC/15 A

Input

Supply voltage for DC Rated value	24 V
Voltage curve at input	DC
input voltage range	22 ... 29 V DC

Mains buffering

Type of energy storage	with batteries
Charging current	
• 1	0.35 A
• 2	0.7 A

Output

Output voltage	
• in normal operation for DC Rated value	24 V
• in buffering mode for DC Rated value	24 V
Formula for output voltage	$V_{in} - \text{approx. } 0.5 \text{ V}$
ON-delay time typical	1 s
Voltage increase time of the output voltage typical	60 ms
Output current Rated value	15 A
Property of the output Short-circuit proof	Yes
Active power supplied typical	360 W

Efficiency

Efficiency in percent	
• at rated output current at rated output current typical	96.2 %
• in case of accumulator operation typical	96 %

Active power loss		
<ul style="list-style-type: none"> • at rated output current at rated output current typical • in case of accumulator operation typical 		14 W
		15 W
Protection and monitoring		
Product function		
<ul style="list-style-type: none"> • reverse polarity protection against energy storage unit polarity reversal • reverse polarity protection against input voltage polarity reversal 		Yes
		Yes
Signaling		
Display version		
<ul style="list-style-type: none"> • for normal operation 		Normal operation: LED green (OK), floating changeover contact "Bat/OK" to setting "OK" ("OK" means: Voltage of the supplying power supply unit is greater than cut-in threshold set at the DC UPS module); Lack of buffer standby: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Battery replacement required: LED red (alarm) flashing with approx. 0.25 Hz, floating changeover contact "Alarm/Bat" switching with approx. 0.25 Hz; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed; Permissible contact current capacity: DC 60 V/1 A or AC 30 V /1 A
<ul style="list-style-type: none"> • in buffering mode 		Buffered mode: LED yellow (Bat), floating changeover contact "OK/Bat" to setting "Bat"; Prewarning battery voltage < 20.4 VDC: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed
Interface		
Product component PC interface		No
Design of the interface		without
Safety		
Galvanic isolation between entrance and outlet		No
Operating resource protection class		Class III
Certificate of suitability		
<ul style="list-style-type: none"> • CE marking • UL approval • as approval for USA • relating to ATEX • C-Tick 		<p>Yes</p> <p>Yes</p> <p>cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259</p> <p>-</p> <p>No</p>
Shipbuilding approval		-
Protection class IP		IP20
EMC		
Standard		

- for emitted interference
- for interference immunity

EN 55022 Class B

EN 61000-6-2

Operating data

Ambient temperature

- during operation -25 ... +60 °C
- during transport -40 ... +85 °C
- during storage -40 ... +85 °C

Mechanics

Type of electrical connection	screw-type terminals
• at input	24 V DC: 2 screw terminals for 1 ... 4 mm ² /17 ... 11 AWG
• at output	24 V DC: 4 screw terminals for 1 ... 4 mm ² /17 ... 11 AWG
• for battery module	24 V DC: 2 screw terminals for 1 ... 4 mm ² /17 ... 11 AWG
• for control circuit and status message	10 screw terminals for 0.5 ... 2.5 mm ² /20 ... 13 AWG
Width of the enclosure	50 mm
Height of the enclosure	125 mm
Depth of the enclosure	125 mm
Required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
Net weight	0.4 kg
Product property of the enclosure housing for side-by-side mounting	Yes
Mounting type	Snaps onto DIN rail EN 60715 35x7.5/15
Electrical accessories	Battery module
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)