

PanelView Plus 7 Performance Terminals

Catalog Numbers 2711P-xxx22x9P, 2711P-xxx22x9P-B, 2711P-xxx22x9PK, 2711P-Txx22D9P-BSHK, 2711P-T12W22D9P-BMxxx

Topic	Page
Summary of Changes	2
Catalog Numbers	2
Environmental Specifications	3
Resistance to Chemicals	4
Certifications	4
Technical Specifications	5
PanelView Plus 7 Performance Terminals	5
PanelView Plus 7 Performance Stainless Steel Terminals	8
ArmorView Plus 7 Terminals	9
Accessories	13
HMI Software	15
Additional Resources	15

The PanelView™ Plus 7 Performance terminals are operator interface devices. They monitor and control devices that are attached to ControlLogix® and CompactLogix™ 5370 controllers on an EtherNet/IP™ network. Animated graphic and text displays provide operators a view into the operating state of a machine or process. Operators interact with the control system by using touch screen or keypad input.

The PanelView Plus 7 Performance terminals include these features and capabilities:

- FactoryTalk® View Machine Edition software provides a familiar environment for creating HMI applications
- Connection to ControlLogix or CompactLogix 5370 controllers
- Ethernet communication that can support Device Level Ring (DLR), linear, or star network topologies
- Conformal coating available for all DC power, touch-only terminals, and the 15-in. DC power, keypad and touch terminal
- Stainless steel, hygienic, brandless, DC-power, and conformal coating are available for the touch-only units in the 9-in. wide screen, 10-in., 12-in. wide screen, and 15-in. terminal sizes
- On-machine mounting available for the 12.1-in. wide screen, touch-only terminals



Summary of Changes

This publication contains new and updated information as indicated in the following table.

Topic	Page
Added 10-in. and 15-in. stainless steel catalog numbers and information	Throughout
Corrected the Corrosive Atmosphere rating information in the Environmental Specifications table	3
Updated the CE (LVD), KDD, and RoHS information in the Certifications table	4

Catalog Numbers

This publication is applicable to these currently available PanelView Plus 7 Performance terminals.

PanelView Plus 7 Performance	2711P-T7C22D9P, 2711P-B7C22D9P, 2711P-T9W22D9P, 2711P-T10C22D9P, 2711P-B10C22D9P, 2711P-T12W22D9P, 2711P-T15C22D9P, 2711P-B15C22D9P, 2711P-T19C22D9P
PanelView Plus 7 Performance Conformal Coated	2711P-T7C22D9PK, 2711P-T9W22D9PK, 2711P-T10C22D9PK, 2711P-T12W22D9PK, 2711P-T15C22D9PK, 2711P-T19C22D9PK
PanelView Plus 7 Performance Brandless	2711P-T7C22D9P-B, 2711P-B7C22D9P-B, 2711P-T9W22D9P-B, 2711P-T10C22D9P-B, 2711P-B10C22D9P-B, 2711P-T12W22D9P-B, 2711P-T15C22D9P-B, 2711P-T19C22D9P-B
PanelView Plus 7 Performance Stainless Steel	2711P-T9W22D9P-BSHK, 2711P-T10C22D9P-BSHK, 2711P-T12W22D9P-BSHK, 2711P-T15C22D9P-BSHK
ArmorView Plus 7	2711P-T12W22D9P-BM001, 2711P-T12W22D9P-BM002, 2711P-T12W22D9P-BM003, 2711P-T12W22D9P-BM004, 2711P-T12W22D9P-BM005, 2711P-T12W22D9P-BM006, 2711P-T12W22D9P-BM007, 2711P-T12W22D9P-BM008, 2711P-T12W22D9P-BM009, 2711P-T12W22D9P-BM010, 2711P-T12W22D9P-BM011, 2711P-T12W22D9P-BM012, 2711P-T12W22D9P-BM013, 2711P-T12W22D9P-BM014, 2711P-T12W22D9P-BM015, 2711P-T12W22D9P-BM016

This publication is also applicable to these discontinued PanelView Plus 7 Performance terminals.

PanelView Plus 7 Performance	2711P-T7C22A9P, 2711P-B7C22A9P, 2711P-T9W22A9P, 2711P-T10C22A9P, 2711P-B10C22A9P, 2711P-T12W22A9P, 2711P-T15C22A9P, 2711P-B15C22A9P, 2711P-T19C22A9P
PanelView Plus 7 Performance Brandless	2711P-T7C22A9P-B, 2711P-B7C22A9P-B, 2711P-T9W22A9P-B, 2711P-T10C22A9P-B, 2711P-B10C22A9P-B, 2711P-T12W22A9P-B, 2711P-T15C22A9P-B, 2711P-B15C22A9P-B, 2711P-T19C22A9P-B

PanelView Plus 7 Performance terminal catalog numbers ending in:

- 'K' are conformal coated for extended protection in harsh, corrosive environments
- '-B' exclude the Allen-Bradley brand marking. You can put your own brand labels on these terminals
- 'BSHK' are conformal coated, brandless, and feature a stainless-steel 316 bezel

Technical Specifications - PanelView Plus 7 Performance 10-in and 12-in Terminals

Attribute	10.4-in. Touch		10.4-in. Touch with Keypad		12.1-in. Touch			
	2711P-T10C22D9P, 2711P-T10C22D9P-B, 2711P-T10C22D9PK	2711P-T10C22A9P, 2711P-T10C22A9P-B	2711P-B10C22D9P, 2711P-B10C22D9P-B	2711P-B10C22A9P, 2711P-B10C22A9P-B	2711P-T12W22D9P, 2711P-T12W22D9P-B, 2711P-T12W22D9PK	2711P-T12W22A9P, 2711P-T12W22A9P-B		
Operator input	Touch		Touch with keypad		Touch			
Display type	TFT Color							
Display size, diagonal	10.4-in.			12.1-in. wide screen				
Viewing area (W x H)	211 x 158 mm (8.3 x 6.2 in.)			281 x 163 mm (10.3 x 6.4 in.)				
Display resolution	(Series A) 800 x 600 VGA, 18-bit color graphics			(Series A) 1280 x 800 WXGA, 18-bit color graphics				
Display resolution	(Series B) 800 x 600 VGA, 24-bit color graphics			(Series B) 1280 x 800 WXGA, 24-bit color graphics				
Aspect ratio	4:3			16:10				
Brightness, typical	300 cd/m ² (Nits) or more							
Backlight life	White light-emitting diode, solid-state Life: 50,000 h min at 40 °C (104 °F) to half-brightness, backlight is not replaceable							
Touch screen	Analog resistive Actuation rating: 1 million presses Operating force: 100 grams							
Battery (real-time clock backup)	Accuracy: ±2 minutes per month. Battery life: 4 years min at 25 °C (77 °F) Replacement: CR2032 lithium coin cell							
Memory:	(Series A) 512 MB RAM and 512 MB storage 80 MB, approx, nonvolatile storage for applications			(Series B) 4 GB RAM and 19.87 GB storage 2 GB, approx, nonvolatile storage for applications				
Secure Digital (SD) card slot	One SD card slot for external storage; supports cat. no. 1784-SDx and 1784-SDHCx cards							
USB ports:	(Series A) Two USB high-speed 2.0 host ports (type A) support removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release			(Series B) One USB high-speed 3.0 host port and one USB 2.0 host port (Type A) supports removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release				
Operating system	Windows CE 6.0 with Extended Features and Microsoft Office Viewers (includes FTP, VNC client server, ActiveX controls, PDF reader, third-party device support)			(Series B) Windows 10 IoT Core				
Ethernet ports	Two 10/100Base-T, Auto MDI/MDIX Ethernet ports that support Device Level Ring (DLR), linear, or star network topologies							
Software	FactoryTalk View Studio for Machine Edition, FactoryTalk ViewPoint, version 2.6 or later							
Input voltage	24V DC nom (18...30V DC)	100...240V AC	24V DC nom (18...30V DC)	100...240V AC	24V DC nom (18...30V DC)	100...240V AC		
Power consumption	(Series A) 50 W max (2.1 A at 24V DC) (Series B) 32 W max	105VA	(Series A) 50 W max (2.1 A at 24V DC) (Series B) 32 W max	105VA	(Series A) 50 W max (2.1 A at 24V DC) (Series B) 33 W max	105VA		
Power supply	Supports (SELV) and (PELV) 24V DC supplies ⁽¹⁾	—	Supports (SELV) and (PELV) 24V DC supplies ⁽¹⁾	—	Supports (SELV) and (PELV) 24V DC supplies ⁽¹⁾	—		
Weight, approx	2.28 kg (5.03 lb)		2.58 kg (5.69 lb)		2.54 kg (5.60 lb)			
Dimensions, approx (H x W x D)	252 x 297 x 69.6 mm (9.92 x 11.69 x 2.74 in.)		252 x 385 x 69.6 mm (9.92 x 15.16 x 2.74 in.)		240 x 340 x 69.6 mm (9.69 x 13.39 x 2.74 in.)			
Cutout dimensions, approx (H x W)	224 x 269 mm (8.82 x 10.59 in.)		224 x 335 mm (8.82 x 13.19 in.)		218 x 312 mm (8.58 x 12.28 in.)			

(1) DC-powered terminals support safety extra low voltage (SELV) and protective extra low voltage (PELV) 24V DC power supplies such as cat. nos. 1606-XLP95E, 1606-XLP100E, 2711P-RSACDIN.

Technical Specifications - PanelView Plus 7 Performance 15-in and 19-in Terminals

Attribute	15-in. Touch		15-in. Touch with Keypad		19-in. Touch			
	2711P-T15C22D9P, 2711P-T15C22D9P-B, 2711P-T15C22D9PK	2711P-T15C22A9P, 2711P-T15C22A9P-B	2711P-B15C22D9P, 2711P-B15C22D9P-B, 2711P-B15C22D9PK	2711P-B15C22A9P, 2711P-B15C22A9P-B	2711P-T19C22D9P, 2711P-T19C22D9P-B, 2711P-T19C22D9PK	2711P-T19C22A9P, 2711P-T19C22A9P-B		
Operator input	Touch		Touch with keypad		Touch			
Display type	TFT Color							
Display size, diagonal	15-in.			19-in.				
Viewing area (W x H)	304 x 228 mm (12.0 x 9.0 in.)			376 x 301 mm (14.8 x 11.9 in.)				
Display resolution	(Series A) 1024 x 768 XGA, 18-bit color graphics			(Series A) 1280 x 1024 SXGA, 18-bit color graphics				
	(Series B) 1024 x 768 XGA, 24-bit color graphics			(Series B) 1280 x 1024 SXGA, 24-bit color graphics				
Aspect ratio	4:3			5:4				
Brightness, typical	300 cd/m ² (nits) or more							
Backlight life	White light-emitting diode, solid-state Life: 50,000 h min at 40 °C (104 °F) to half-brightness, backlight is not replaceable							
Touch screen	Analog resistive Actuation rating: 1 million presses Operating force: 100 grams							
Battery (real-time clock backup)	Accuracy: ±2 minutes per month. Battery life: 4 years min at 25 °C (77 °F) Replacement: CR2032 lithium coin cell							
Memory:	(Series A) 512 MB RAM and 512 MB storage 80 MB, approx, nonvolatile storage for applications			(Series B) 4 GB RAM and 19.87 GB storage 2 GB, approx, nonvolatile storage for applications				
Memory: • System • User								
Secure Digital (SD) card slot	One SD card slot for external storage; supports cat. no. 1784-SDx and 1784-SDHCx cards							
USB ports: • Host • Device	(Series A) Two USB high-speed 2.0 host ports (type A) support removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release			(Series B) One USB high-speed 3.0 host port and one USB 2.0 host port (Type A) supports removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release				
Operating system	Windows CE 6.0 with Extended Features and Microsoft Office Viewers (includes FTP, VNC client server, ActiveX controls, PDF reader, third-party device support)			(Series B) Windows 10 IoT Core				
Ethernet ports	Two 10/100Base-T, Auto MDI/MDIX Ethernet ports that support Device Level Ring (DLR), linear, or star network topologies							
Software	FactoryTalk View Studio for Machine Edition, FactoryTalk ViewPoint, version 2.6 or later							
Input voltage	24V DC nom (18...30V DC)	100...240V AC	24V DC nom (18...30V DC)	100...240V AC	24V DC nom (18...30V DC)	100...240V AC		
Power consumption	(Series A) 50 W max (2.1 A at 24V DC) (Series B) 39 W max	105VA	(Series A) 50 W max (2.1 A at 24V DC) (Series B) 39 W max	105VA	(Series A) 50 W max (2.1 A at 24V DC) (Series B) 45 W max	105VA		
Power supply	Supports (SELV) and (PELV) 24V DC supplies ⁽¹⁾	—	Supports (SELV) and (PELV) 24V DC supplies ⁽¹⁾	—	Supports (SELV) and (PELV) 24V DC supplies ⁽¹⁾	—		
Weight, approx	3.69 kg (8.14 lb)		4.14 kg (9.13 lb)		5.62 kg (12.40 lb)			
Dimensions, approx (H x W x D)	318 x 381 x 69.6 mm (12.52 x 15.00 x 2.74 in)		322 x 484 x 69.6 mm (12.68 x 19.06 x 2.74 in)		411 x 485 x 69.6 mm (16.18 x 19.09 x 2.74 in)			
Cutout dimensions, approx (H x W)	290 x 353 mm (11.42 x 13.90 in)		290 x 418 mm (11.42 x 16.46 in)		383 x 457 mm (15.08 x 17.99 in)			

(1) DC-powered terminals support safety extra low voltage (SELV) and protective extra low voltage (PELV) 24V DC power supplies such as cat. nos. 1606-XLP95E, 1606-XLP100E, 2711P-RSACDIN.

PanelView Plus 7 Performance Stainless Steel Terminals

Technical Specifications - PanelView Plus 7 Performance Stainless Steel Terminals

Attribute	9-in. Touch 271IP-T9W22D9P-BSHK	10.4-in. Touch 271IP-T10C22D9P-BSHK	12.1-in. Touch 271IP-T12W22D9P-BSHK	15-in. Touch 271IP-T15C22D9P-BSHK
Operator input			Touch	
Display type			TFT Color	
Display size, diagonal	9-in. wide screen	10.4-in. screen	12.1-in. wide screen	15-in. screen
Viewing area (W x H)	196 x 118 mm (7.7 x 4.6 in.)	211 x 158 mm (8.3 x 6.2 in.)	261 x 163 mm (10.3 x 6.4 in.)	304 x 228 mm (12.0 x 9.0 in.)
Display resolution	(Series B) 800 x 480 WVGA, 18-bit color graphics (Series C) 800 x 480 WVGA, 24-bit color graphics	(Series C) 800 x 600 SVGA, 24-bit color graphics	(Series B) 1280 x 800 WXGA, 18-bit color graphics (Series C) 1280 x 800 WXGA, 24-bit color graphics	(Series C) 1024 x 768 XGA, 24-bit color graphics
Aspect ratio	5:3	4:3	16:10	4:3
Brightness, typical		300 cd/m ² (nits) or more		
Backlight life		White light-emitting diode, solid-state Life: 50,000 h min at 40 °C (104 °F) to half-brightness, backlight is not replaceable		
Touch screen		Analog resistive Actuation rating: 1 million presses Operating force: 100 grams		
Battery (real-time clock backup)		Accuracy: ±2 minutes per month Battery life: 4 years min at 25 °C (77 °F) Replacement: CR2032 lithium coin cell		
Memory: • System • User	(Series B) 512 MB RAM and 512 MB storage 80 MB, approx, nonvolatile storage for applications (Series C) 4 GB RAM and 19.87 GB storage 2 GB, approx, nonvolatile storage for applications	(Series C) 4 GB RAM and 19.87 GB storage 2 GB, approx, nonvolatile storage for applications	(Series B) 512 MB RAM and 512 MB storage 80 MB, approx, nonvolatile storage for applications (Series C) 4 GB RAM and 19.87 GB storage 2 GB, approx, nonvolatile storage for applications	(Series C) 4 GB RAM and 19.87 GB storage 2 GB, approx, nonvolatile storage for applications
Secure Digital (SD) card slot		One SD card slot for external storage; supports cat. no. 1784-SDx and 1784-SDHCx cards		
USB ports: • Host • Device	(Series B) Two USB high-speed 2.0 host ports (type A) support removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release (Series C) One USB high-speed 3.0 host port and one USB 2.0 host port (Type A) supports removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release	(Series C) One USB high-speed 3.0 host port and one USB 2.0 host port (Type A) supports removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release	(Series B) Two USB high-speed 2.0 host ports (type A) support removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release (Series C) One USB high-speed 3.0 host port and one USB 2.0 host port (Type A) supports removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release	(Series C) One USB high-speed 3.0 host port and one USB 2.0 host port (Type A) supports removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release
Operating system	(Series B) Windows CE 6.0 with Extended Features and Microsoft Office Viewers (includes FTP, VNC client server, ActiveX controls, PDF reader, third-party device support) (Series C) Windows 10 IoT Core	(Series C) Windows 10 IoT Core	(Series B) Windows CE 6.0 with Extended Features and Microsoft Office Viewers (includes FTP, VNC client server, ActiveX controls, PDF reader, third-party device support) (Series C) Windows 10 IoT Core	(Series C) Windows 10 IoT Core
Ethernet ports		Two 10/100Base-T, Auto MDI/MDIX Ethernet ports that support Device Level Ring (DLR), linear, or star network topologies		
Software		FactoryTalk View Studio for Machine Edition, FactoryTalk ViewPoint, version 2.6 or later		
Input voltage		24V DC nom (18...30V DC)		
Power consumption	(Series B) 50 W max (2.1 A at 24V DC) (Series C) 30 W max	(Series C) 32 W max	(Series B) 50 W max (2.1 A at 24V DC) (Series C) 33 W max	(Series C) 39 W max
Power supply		Supports (SELV) and (PELV) 24V DC supplies ⁽¹⁾		
Stainless-steel bezel		316 stainless steel with hygienic No. 4 finish		
Silicone gasket		Gasket material is compliant with FDA 21 CFR 177.2600		
Weight, approx	2.1 kg (4.6 lb)	3.25 kg (7.2 lbs)	3.7 kg (8.2 lb)	4.7 kg (10.4 lbs)
Dimensions, approx (H x W x D)	190 x 280 x 69.6 mm (7.48 x 11.02 x 2.74 in.)	252 x 297 x 69.6 mm (9.92 x 11.69 x 2.74 in.)	240 x 340 x 69.6 mm (9.69 x 13.39 x 2.74 in.)	318 x 381 x 69.6 mm (12.52 x 15.00 x 2.74 in)
Cutout dimensions, approx (H x W)	162 x 252 mm (6.38 x 9.92 in.)	224 x 269 mm (8.82 x 10.59 in.)	218 x 312 mm (8.58 x 12.28 in.)	290 x 353 mm (11.42 x 13.90 in)

(1) DC-powered terminals support safety extra low voltage (SELV) and protective extra low voltage (PELV) 24V DC power supplies such as cat. nos. 1606-XLP95E, 1606-XLP100E, 271IP-RSACDIN.

ArmorView Plus 7 Terminals

Technical Specifications - ArmorView Plus 7 Terminals

Attribute	12.1 in. Touch		
	2711P-T12W22D9P-BM001, 2711P-T12W22D9P-BM002	2711P-T12W22D9P-BM003...2711P-T12W22D9P-BM016	
Operator input	Touch	Touch screen and push button, selector switches, or keyswitches	
Display type		TFT Color	
Display size, diagonal		12.1-in. wide screen	
Viewing area (W x H)		261 x 163 mm (10.3 x 6.4 in.)	
Display resolution	(Series A) 1280 x 800 WXGA, 18-bit color graphics		
	(Series B) 1280 x 800 WXGA, 24-bit color graphics		
Aspect ratio		16:10	
Brightness, typical		300 cd/m ² (nits) or more	
Backlight life		White light-emitting diode, solid-state Life: 50,000 h min at 40 °C (104 °F) to half-brightness, backlight is not replaceable	
Touch screen		Analog resistive Actuation rating: 1 million presses Operating force: 100 grams	
E-stop	—	Illuminated twist-to-release 300,000 cycles	
Push buttons	—	Momentary push buttons 10,000,000 cycles	
Selector switches	—	Two-position selector, three-position selector, three-position key selector 1,000,000 cycles	
Battery (real-time clock backup)		Accuracy: ±2 minutes per month Battery life: 4 years min at 25 °C (77 °F) Replacement: CR2032 lithium coin cell	
Memory: • System • User	(Series A) 512 MB RAM and 512 MB storage 80 MB, approx, nonvolatile storage for applications		
	(Series B) 4 GB RAM and 19.87 GB storage 2 GB, approx, nonvolatile storage for applications		
Secure Digital (SD) card slot		One SD card slot for external storage; supports cat. nos. 1784-SDx and 1784-SDHCx cards	
USB ports: • Host • Device	(Series A) Two USB high-speed 2.0 host ports (type A) support removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release		
	(Series B) One USB high-speed 3.0 host port and one USB 2.0 host port (Type A) supports removable flash drives for external storage One high-speed 2.0 device port (type B) that will be functional in a future release		
Operating system	(Series A) Windows CE 6.0 with Extended Features and MS Office Viewers (includes FTP, VNC client server, ActiveX controls, PDF reader, third-party device support)		
	(Series B) Windows 10 IoT Core		
Ethernet ports		Two 10/100Base-T, Auto MDI/MDIX Ethernet ports that support Device Level Ring (DLR), linear, or star network topologies	
Software		FactoryTalk View Studio for Machine Edition, FactoryTalk ViewPoint, version 2.6 or later	
Input voltage		24V DC nom (18...30V DC)	
Power consumption		37 W max (1.54 A at 24V DC)	
Power supply		Supports (SELV) and (PELV) 24V DC supplies ⁽¹⁾	
Weight, approx (with arm adapter)		7.41 kg (16.34 lb)	
Weight, approx (with VESA Kit)		8.19 kg (18.06 lb)	
Dimensions with arm adapter, approx (H x W x D)		381.6 x 345 x 166.6 mm (15.02 x 13.58 x 6.56 in.)	
Dimensions with I/O plate, approx (H x W x D)		345 x 345 x 166.6 mm (13.58 x 13.58 x 6.56 in.)	

(1) DC-powered terminals support safety extra low voltage (SELV) and protective extra low voltage (PELV) 24V DC power supplies such as cat. nos. 1606-XLP95E, 1606-XLP100E, 2711P-RSACDIN.