

### Product type designation

### CP 443-1

Communications processor CP 443-1; 2x 10/100 Mbit/s (IE switch); RJ45 ports; ISO; TCP; UDP; PROFINET IO controller; S7 communication; Open communication (SEND/ RECEIVE); S7 routing; IP configuration via DHCP/ Block; IP Access Control List; Time synchronization; extended web diagnostics; Fast Startup; Support for PROFINergy;



### Transfer rate

#### Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

### Interfaces

Number of interfaces / acc. to Industrial Ethernet

2

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet

2

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet

RJ45 port

design of the removable storage / C-PLUG

No

### Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Relative symmetrical tolerance / at DC

- at 5 V

5 %

Consumed current

- from backplane bus / at DC / at 5 V / typical

1.4 A

Power loss [W]	7.25 W
----------------	--------

### Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	0 ... 60 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +70 °C
Relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
Protection class IP	IP20

### Design, dimensions and weights

Module format	Compact module S7-400 single width
Width	25 mm
Height	290 mm
Depth	210 mm
Net weight	0.7 kg

### Product features, product functions, product components / general

Number of units	
<ul style="list-style-type: none"> <li>per CPU / maximum</li> </ul>	14
<ul style="list-style-type: none"> <li>Note</li> </ul>	max. 4 as PN IO ctrl.

### Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	64
Amount of data	
<ul style="list-style-type: none"> <li>as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	2 Kibyte
Number of possible connections / for open communication	
<ul style="list-style-type: none"> <li>by means of T blocks / maximum</li> </ul>	64
Amount of data	

- as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum

1452 byte

#### Performance data / S7 communication

Number of possible connections / for S7 communication

- maximum
- with PG connections / maximum
- Note

128

2

when using several CPUs

#### Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode

128

#### Performance data / PROFINET communication / as PN IO controller

Product function / PROFINET IO controller

Yes

Number of PN IO devices / on PROFINET IO controller / usable / total

128

Number of PN IO IRT devices / on PROFINET IO controller / usable

64

Number of external PN IO lines / with PROFINET / per rack

4

Amount of data

- as user data for input variables / as PROFINET IO controller / maximum
- as user data for input variables / as PROFINET IO controller / maximum
- as user data for input variables per PN IO device / as PROFINET IO controller / maximum
- as user data for output variables per PN IO device / as PROFINET IO controller / maximum
- as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum
- as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum

4 Kibyte

4 Kibyte

1433 byte

1433 byte

240 byte

240 byte

#### Product functions / management, configuration, engineering

Product function / MIB support

Yes

Protocol / is supported

- SNMP v1
- DCP
- LLDP

Yes

Yes

Yes

Configuration software

- required

STEP 7 V5.5 SP3 or higher / STEP 7 Professional V12 (TIA Portal) or higher

### Product functions / Diagnostics

Product function / Web-based diagnostics Yes

### Product functions / Switch

Product feature / Switch Yes

Product function

- switch-managed No
- with IRT / PROFINET IO switch Yes
- Configuration with STEP 7 Yes

### Product functions / redundancy

Product function

- Ring redundancy Yes
- Redundancy manager Yes

Protocol / is supported / Media Redundancy Protocol (MRP) Yes

### Product functions / Security

Product function

- password protection for Web applications No
- ACL - IP-based Yes
- ACL - IP-based for PLC/routing No
- switch-off of non-required services Yes
- Blocking of communication via physical ports Yes
- log file for unauthorized access No

### Product functions / time

Product function / SICLOCK support Yes

Product function / pass on time synchronization Yes

Protocol / is supported

- NTP Yes

### Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

### Security information