



## Legacy PanelView Terminals to PanelView Plus 7 Terminals Catalog Number Conversions

Topic	Page
About This Publication	1
Summary of Changes	2
Application Migration	2
Catalog Number Explanations	3
Catalog Number Conversion Tables	10
PanelView Standard 300 and 300 Micro Terminals Conversions	10
PanelView Standard 550 Terminals Conversions	11
PanelView Standard 600 Terminals Conversions	15
PanelView Standard 900 Terminals Conversions	19
PanelView Standard 1000 Terminals Conversions	25
PanelView Standard 1400 Terminals Conversions	31
PanelView Enhanced 1000e, 1200e, and 1400e Terminals Conversions	33
Accessories	34
Legacy Communication Support	34
Adapter Kit Conversion Table	35
Additional Resources	35

### About This Publication

This publication provides information to help you convert legacy 2711 PanelView™ Standard terminals and 2711E PanelView Enhanced terminals to these new generation terminals:

- PanelView Plus 7 Standard terminals
- PanelView Plus 7 Performance terminals

PanelView Standard 1000 Terminals Secondary Replacement Options (Continued)

PanelView Standard Terminals						PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Plate Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
1000	2711-K10G9	390 (15.35)		640 x 480	RS-232 (DH-485)	2711P-B15C22A9P	290 (11.42)	418 (16.46)	1024 x 768	Dual Ethernet ports	N/A	PanelView Plus 7 Performance 15-in. terminal benefits: • Higher resolution • DLR Communication = Ethernet. Operator input = The 15-in. terminal is listed as secondary replacement if you require a keypad. Power input = AC or DC. <sup>(1)</sup> Conformal coat = No. <sup>(2)</sup>
	2711-K10G9L1				2711P-B15C22D9P							
	2711-K10G8				2711P-B15C22A9P							
	2711-K10G8L1				2711P-B15C22D9P							
	2711-K10G20				2711P-B15C22A9P							
	2711-K10G20L1	2711P-B15C22D9P										
	2711-T10C1	257 (10.11)		640 x 480	Remote I/O	No secondary option available.						
	2711-T10C1L1											
	2711-T10C10											
	2711-T10C10L1											
	2711-T10C14											
	2711-T10C14L1											
	2711-T10C12											
	2711-T10C12L1											
	2711-T10C16											
	2711-T10C16L1											
	2711-T10C15											
	2711-T10C15L1											
	2711-T10C3											
	2711-T10C3L1											
	2711-T10C9				338 (13.29)							
	2711-T10C9L1	DH+										
	2711-T10C8	Ethernet										
	2711-T10C8L1	Remote I/O										
	2711-T10C20	DeviceNet										
	2711-T10C20L1											
	2711-T10G1											
	2711-T10G1L1	RS-232										
	2711-T10G10											
	2711-T10G10L1											
	2711-T10G14											
	2711-T10G14L1	RS-232 (DF1)										
	2711-T10G12											
2711-T10G12L1												
2711-T10G16	RS-232 (DF1)											

**PanelView Standard 1000 Terminals Secondary Replacement Options (Continued)**

PanelView Standard Terminals						PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Plate Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
1000	2711-T10G16L1	257 (10.11)	338 (13.29)	640 x 480	RS-232 (DF1)							No secondary option available.
	2711-T10G15				ControlNet							
	2711-T10G15L1											
	2711-T10G3				DH-485							
	2711-T10G3L1											
	2711-T10G9				RS-232 (DH-485)							
	2711-T10G9L1											
	2711-T10G8				DH+							
	2711-T10G8L1											
	2711-T10G20											
	2711-T10G20L1				Ethernet							

<sup>(1)</sup> AC power is only available on Series A terminals. DC power is only available on Series B terminals.

<sup>(2)</sup> Conformal coating is available for the DC power, touch models (and the 15-in. DC power combination keypad/touch model) of the PanelView Plus 7 Performance family. To order a terminal that is conformal-coated, add K to the end of a DC-power catalog number; for example, 2711P-B1522D9PK.