

Migrating PanelView Standard Applications to PanelView Plus 7



PanelView Standard 600 Terminals Conversions

See the tables in this section for primary and secondary conversions for PanelView Standard 600 terminals.

PanelView Standard 600 Terminals Primary Replacement Options

PanelView Standard Terminals					PanelView Plus 7 Terminals – Primary Replacement Options							
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Kit Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
600	2711-K6C1	192 (7.55)	290 (11.40)	320 x 234	Remote I/O	2711P-B7C22A9P ⁽¹⁾	142 (5.59)	237 (9.33)	640 x 480	Dual Ethernet ports	2711P-RAAK7	PanelView Plus 7 Performance 6.5 in. terminals benefits: • Higher resolution • DLR Communication = Ethernet. Operator input = keypad and touch. Power input = AC or DC. ⁽¹⁾ Conformal coat = No. Adapter kit is necessary for drop-in replacement.
	2711-K6C1L1				2711P-B7C22D9P							
	2711-K6C10				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C10L1				2711P-B7C22D9P							
	2711-K6C14				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C14L1				2711P-B7C22D9P							
	2711-K6C12				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C12L1				2711P-B7C22D9P							
	2711-K6C16				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C16L1				2711P-B7C22D9P							
	2711-K6C15				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C15L1				2711P-B7C22D9P							
	2711-K6C2				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C2L1				2711P-B7C22D9P							
	2711-K6C3				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C3L1				2711P-B7C22D9P							
	2711-K6C5				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C5L1				2711P-B7C22D9P							
	2711-K6C9				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C9L1				2711P-B7C22D9P							
	2711-K6C8				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C8L1				2711P-B7C22D9P							
	2711-K6C20				2711P-B7C22A9P ⁽¹⁾							
	2711-K6C20L1				2711P-B7C22D9P							
	2711-B6C1				2711P-B7C22A9P ⁽¹⁾							
	2711-B6C1L1				2711P-B7C22D9P							
	2711-B6C10				2711P-B7C22A9P ⁽¹⁾							
	2711-B6C10L1				2711P-B7C22D9P							
	2711-B6C14				2711P-B7C22A9P ⁽¹⁾							
	2711-B6C14L1				2711P-B7C22D9P							
	2711-B6C12				2711P-B7C22A9P ⁽¹⁾							
	2711-B6C12L1				2711P-B7C22D9P							
2711-B6C16	2711P-B7C22A9P ⁽¹⁾											
2711-B6C16L1	2711P-B7C22D9P											

PanelView Standard 600 Terminals Secondary Replacement Options

PanelView Standard Terminals						PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Kit Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
600	2711-K6C1	192 (7.55)	290 (11.40)	320 x 234	Remote I/O	2711P-T7C21D8S	142 (5.59)	184 (7.24)	640 x 480	One Ethernet port	N/A	PanelView Plus 7 Standard 6.5 in. terminal benefits: Higher resolution Application limits: • Max. screen count: 100 • Max. alarm messages: 500 • Max. number of controllers: 1 Communication = Ethernet (dual Ethernet ports are available). Operator input = only touch. Power input = only DC. Conformal coat = No.
	2711-K6C1L1											
	2711-K6C10											
	2711-K6C10L1											
	2711-K6C14				DeviceNet							
	2711-K6C14L1											
	2711-K6C12				RS-232							
	2711-K6C12L1											
	2711-K6C16				RS-232 (DF1)							
	2711-K6C16L1											
	2711-K6C15				ControlNet							
	2711-K6C15L1											
	2711-K6C2											
	2711-K6C2L1				DH-485							
	2711-K6C3											
	2711-K6C3L1											
	2711-K6C5				RS-232 (DH-485)							
	2711-K6C5L1											
	2711-K6C9											
	2711-K6C9L1											
	2711-K6C8				DH+							
	2711-K6C8L1											
	2711-K6C20				EtherNet/IP							
	2711-K6C20L1											
	2711-B6C1				Remote I/O							
	2711-B6C1L1											
	2711-B6C10											
	2711-B6C10L1				DeviceNet							
	2711-B6C14											
	2711-B6C14L1											
2711-B6C12	RS-232											
2711-B6C12L1												
2711-B6C16	RS-232 (DF1)											
2711-B6C16L1												