

product type designation



IE/PB LINK PN IO

IE/PB link PN IO, gateway between Industrial Ethernet and PROFIBUS, PROFINET IO proxy with real-time communication, time-of-day synchronization via SIMATIC processes, NTP, SNMP v1, LLDP, S7 routing, data record routing, connection of up to 64 S7/DPV0/DPV1 slaves, support of DP/PA link and DP/FF link, 10/100 Mbit/s fast Ethernet, MRP, 9.6 Kbit/s up to 12 Mbit/s PROFIBUS, firmware loading via configuration tool, redundant power supply, firmware version V4.0.

product brand name

SIMATIC NET

Technical Product Detail Page

<https://l.siemens.com/1P6GK1411-5AB10>

suitability for operation

Gateway between Industrial Ethernet and PROFIBUS

transfer rate

transfer rate

- | | |
|------------------------|--------------------------|
| • at the 1st interface | 10 ... 100 Mbit/s |
| • at the 2nd interface | 9.6 kbit/s ... 12 Mbit/s |

interfaces

number of electrical connections

- | | |
|---|---|
| • at the 1st interface / according to Industrial Ethernet | 2 |
| • at the 2nd interface / according to PROFIBUS | 1 |
| • for power supply | 2 |

type of electrical connection

- | | |
|---|---|
| • at the 1st interface / according to Industrial Ethernet | RJ45 port onboard or SIMATIC BusAdapter |
|---|---|

type of electrical connection

- | | |
|--|-----------------------------|
| • at the 2nd interface / according to PROFIBUS | 9-pin Sub-D socket (RS 485) |
| • for power supply | 4-pole terminal block |

design of the removable storage

- | | |
|----------|-----|
| • C-PLUG | Yes |
|----------|-----|

supply voltage, current consumption, power loss

type of voltage / of the supply voltage

DC

supply voltage / external / at DC / rated value

24 V

relative positive tolerance / at DC / at 24 V

20 %

relative negative tolerance / at DC / at 24 V

15 %

consumed current

- | | |
|--|-------|
| • from external supply voltage / at DC / at 24 V / typical | 0.2 A |
| • from external supply voltage / at DC / at 24 V / maximum | 0.3 A |

power loss [W]

4.8 W; typical 4.8 W, maximum 7.2 W

ambient conditions

ambient temperature

- | | |
|--|----------------|
| • for vertical installation / during operation | 0 ... 40 °C |
| • for horizontally arranged busbars / during operation | 0 ... 60 °C |
| • during storage | -40 ... +70 °C |
| • during transport | -40 ... +70 °C |

ambient condition / relating to ambient temperature - air pressure - installation altitude

during operation max. 2 000 m above sea level at max. 60 °C ambient temperature

relative humidity

- | | |
|--|------|
| • at 25 °C / without condensation / during operation / | 95 % |
|--|------|

maximum	
protection class IP	IP20
design, dimensions and weights	
module format	ET 200SP design
width	100 mm
height	117 mm
depth	74 mm
net weight	0.6 kg
fastening method	
• 35 mm DIN-rail mounting	Yes
performance data / PROFIBUS DP	
service / as DP master	
• DPV0	Yes
• DPV1	Yes
number of DP devices	
• at the 2nd interface / as DP master / maximum	64
data volume	
• of the address range of the inputs / as DP master / total	2048 byte
• of the address range of the outputs / as DP master / total	2048 byte
• of the address range of the inputs / per DP device	244 byte
• of the address range of the outputs / per DP device	244 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
• maximum	32
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	48
performance data / PROFINET communication / as PN IO device	
product function / PROFINET IO device	Yes
product functions / management, configuration, engineering	
product function / MIB support	Yes
protocol / is supported	
• SNMP v1	Yes
• DCP	Yes
• LLDP	Yes
configuration software	
• required	STEP 7 as of V5.5 SP4 HF11 and HSP, STEP 7 Professional as of V15, PCS7 V9.0, PCS neo as of V3.0, PNI as of V1.0
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 - higher level designation/location designation	Yes
• I&M2 - installation date	Yes
• I&M3 - comment	Yes
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
product functions / routing	
service / as PROFIBUS / data set routing	Yes
number of possible connections / with data set routing / maximum	32
product functions / redundancy	
product function	
• ring redundancy	Yes
product function / of the PROFINET IO device / is supported	
• PROFINET system redundancy	No
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product functions / time	
product function / pass on time synchronization	Yes
protocol / is supported	
• NTP	Yes
• SIMATIC time synchronization (SIMATIC Time)	Yes
standards, specifications, approvals	

certificate of suitability / CE marking	Yes
certificate of suitability / UKCA marking	Yes
certificate of suitability / cULus approval	Yes
certificate of suitability / Regulatory Compliance Mark (RCM)	Yes
certificate of suitability / RoHS conformity	Yes
certificate of suitability / EAC approval	Yes
standards, specifications, approvals / hazardous environments / header	
certificate of suitability / ATEX	Yes
certificate of suitability / IECEx	Yes
certificate of suitability / ULhazloc approval	Yes
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
certificate of suitability / FM registration	Yes
standards, specifications, approvals / marine classification / header	
Marine classification association / American Bureau of Shipping Europe Ltd. (ABS)	Yes
Marine classification association / French marine classification society (BV)	Yes
Marine classification association / Det Norske Veritas (DNV)	Yes
Marine classification association / Lloyds Register of Shipping (LRS)	Yes
Marine classification association / Nippon Kaiji Kyokai (NK)	Yes
Marine classification association / Polski Rejestr Statkow (PRS)	Yes
Marine classification association / Royal Institution of Naval Architects (RINA)	Yes
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
• total	153.97999 kg
• during manufacturing	22.6 kg
• during operation	131 kg
• after end of life	0.38 kg
accessories	
accessories	optional: C-PLUG, SIMATIC BusAdapter of the ET 200SP system
further information / internet links	
internet link	
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to website: Industrial communication	https://www.siemens.com/simatic-net
• to web page: SiePortal	https://sieportal.siemens.com/
• to website: Image database	https://www.automation.siemens.com/bilddb
• to website: CAx-Download-Manager	https://siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7)
Approvals / Certificates	