PRODUCT-DETAILS

3KDE175311L9100

DX910S Digital Input or Output (DIO8-Ex)



General Information

Product ID:	3KDE175311L9100
ABB Type Designation:	DX910S
Catalog Description:	DX910S Digital Input or Output (DIO8-Ex)

© 2026 ABB. All rights reserved.

Long Description:	The remote S900 I/O system can be installed in non-hazardous areas or directly in Zone 1 or Zone 2 hazardous area depending on the selected system variant. S900 I/O communicates with the control system level using PROFIBUS DP standard. The I/O system can be installed directly in the field, therefore the costs for mashalling and wiring are reduced. The system is sturdy, error-tolerant and easy to service. Integrated disconnection mechanisms allow replacement during operation, meaning that there is no need to interrupt the primary voltage in order to exchange the power supply units. S900 I/O type S. For installation in hazardous area Zone 1. For connecting intrinsically safe field devices installed in Zone 2 or Zone 1 or Zone 0. DX910S Digital Input or Output (DI08-Ex), input for dry contacts or proximity switches, output for low power intrinsically safe valves. - ATEX Certification for installation in Zone 1 - Redundancy (Power and Communication) - Hot Configuration in Run - Hot Swap functionality - Extended Diagnostic - Excellent configuration and diagnostics via FDT/DTM - G3-coating for all components - Simplified maintenance with auto-diagnostics - Input for dry contacts or priximity switches (NAMUR) - Output for low power intrinsically safe valves - Short and break detection - Eletrical isolation between input / bus and input / power - Common return for all inputs / outputs - Configurable as a mixture of inputs and outputs - 8 I/O channels
Display Name:	3KDE175311L9100

Additional Information

Medium Description:	Input for dry contact or NAMUR initiator. Output for low power Intrinsic Safe valves.

Ordering

HS Code:	853890 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Parts suitable for use solely or principally with the apparatus of heading|8535, 8536|or 8537;Other

Dimensions

Product Net Depth / Length:	104 mm
Product Net Height:	20 mm
Product Net Width:	104 mm
Product Net Weight:	0.125 kg

Technical

Channel Type:	DX

© 2026 ABB. All rights reserved.

Number of Input Channels:	4
Number of Output Channels:	4

Certificates and Declarations

EU Data Act Compliance Declaration:	7PAA021801
EU Data Act Applicability and Compliance:	2025 Applicable - Compliant

Environmental

RoHS Information:	Following EU Directive 2011/65/EU
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
Number of Batteries:	0
SCIP:	19776d82-3a13-4e99-ba4b-7843b077994c Germany

Categories

Products > Control System Products > I/O Products > S900 I/O > S900 I/O - Modules > DX910S Digital Input or Outputs > DX910S Digital Input or Output

Products > Control Systems > 800xA > I/Os > S900 I/O > I/O Modules

Parts & Services > Control Systems > 800xA > I/Os > S900 I/O > I/O Modules



© 2026 ABB. All rights reserved.